

Pure LED

Ceiling Cord Mounted • Dry Location Listed **PROGRESS LED**

Description:

Pure Collection One-Light LED Pendant

Specifications:

- Satin Aluminum, painted white inside Aluminum Shade
- White Acrylic Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.125 in W., 1.0625 in depth
- Mounting strap for outlet box included
- 120 in of wire supplied

Performance:

Number of Modules	1
Input Power	9 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	323/42.5 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	cCSAus Dry Location Listed

P5175-0930K9




Dimensions:

Diameter: 6-1/2 in
 Height: 8-7/8 in
 Overall Ht. W/Cord: 130 in

Satin Aluminum, painted white inside Aluminum Shade
 Diameter: 6-1/2 in

White Acrylic Diffuser
 Width: 2-7/8 in
 Height: 0-13/16 in



P5175-0930K9

Dimming Notes:

P5175-0930K9 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Nova T NTELV-300

Lutron_Vierti VTELV-600

Lutron_Maestro MAELV-600

Lutron_spacer/system SPSELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.