



Project / Job Name:

Location:

Fixture Type:

Notes:

S11555 - 3.5 Watt; 2G7 Base; 27K/30K/35K/40K CCT Selectable; Frost Finish; Ballast Bypass; 120-277 Volt



GENERAL

Company	SATCO
EA Height	4.84
EA Width	0.91
EA Length	1.54
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Polycarbonate (PC)
Fixture Type	Miniature
Status	Active
Style	Transitional
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.029-0.013A
Has Camera	No
IOT Enabled	No
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	5w/7w/9w

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm to Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	380L/390L/400L/410L
Volts	120V-277V
Watts	3.5W

PHYSICAL

Lamp Base	4-Pin
Finish	Frost
Housing Color	White
ANSI Base	2G7
Lamp Type	PL
MOD Lamps	1.26
MOL	4.74

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	No

PACKAGING

UPC	045923115554
Case Cube	0.3441
Case Height	5.71
Case Length	18.11
Case Quantity	50
Case UPC	10045923115551
Case Weight	5.9
Case Width	5.75
EA Cube	0.0039
EA Height	4.84
EA Length	1.54
EA Quantity	1
EA Weight	0.08
EA Width	0.91
Inner Cube	0.0508
Inner Height	3.46
Inner Length	5.16
Inner Quantity	10
Inner UPC	20045923115558
Inner Weight	1.15
Inner Width	4.92
Pack Type	Box
Web Length	4.74
Web Width	1.26

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No