



Project / Job Name:

Location:

Fixture Type:

Notes:

S29855 - 9 Watt LED PL; 27K/3K/35K/4K CCT Selectable;
G24d Base; Type B; 120-277 Volt



GENERAL

Company	SATCO
EA Height	7.01
EA Width	1.46
EA Length	1.46
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum / Plastic
Fixture Type	Miniature
Status	Active
Style	Transitional
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.075-0.032A
Has Camera	No
IOT Enabled	No
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	18W/26W/32W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	360
Color Temp	Warm to Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1050L/1100L/1150L/1200L
Volts	120V-277V
Watts	9W

PHYSICAL

Lamp Base	G24d (2-Pin)
Finish	Frost
Housing Color	White
ANSI Base	G24d
Lamp Type	PL
MOD Lamps	1.4
MOL	6.9

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923298554
Case Cube	0.28
Case Height	7.95
Case Length	9.33
Case Quantity	24
Case UPC	10045923298551
Case Weight	6.5
Case Width	6.42
EA Cube	0.0086
EA Height	7.01
EA Length	1.46
EA Quantity	1
EA Weight	0.26
EA Width	1.46
Pack Type	Box
Web Length	6.9
Web Width	1.4

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No