



Project / Job Name:

Location:

Fixture Type:

Notes:

S29911-TF - 25 Watt T5 LED; Miniature bi-pin base; 5000K; 50000 Average rated hours; 3500 Lumens; Type A; Ballast dependent; Shatter Proof



GENERAL

Company	SATCO
EA Height	0.59
EA Width	0.59
EA Length	47.6
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required, check compatibility
Lamp Filament	LED
Fixture Type	Linear
Includes	Integrated thermal fuse at pins
Status	Active
Style	Utility
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
Integrated Features	Integrated thermal fuse at pins
IOT Enabled	No
Lens Finish	Gloss
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Shatter Proof Type	Yes
Product Technology	LED
Fluor Equiv	54W
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	185
Color Temp	Natural Light
CRI	80+
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	3500L
Volts	Ballast Dependent
Watts	25W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Gloss
Housing Color	None
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.63
MOL	48.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

Case Cube	0.6247
Case Height	3.54
Case Length	48.4
Case Quantity	10
Case Weight	5.13
Case Width	6.3
EA Cube	0.0096
EA Height	0.59
EA Length	47.6
EA Quantity	1
EA Weight	0.1
EA Width	0.59
Pack Type	Sleeve
Web Length	48.0
Web Width	0.63

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No